

Specifications	2 Bale	2 Bale	2 Bale	2 Bale	2 Bale	2 Bale	2 Bale
MODELS	Double Curve	RS2	Single Shredder	Twin Shredder	Trough Feeder	2B Multi Feeder	3 Bale / 2 Bale - 3B/2B
FEED-OUT TYPE	Bi directional chain - on symetrical high curve - ideal for all chopped round bales	Bi directional chain - on symetrical low curve - Retarder bar fitted to both sides for square bales	Bi directional chain - teasing rota shredder on near side - high curve on off side	Bi directional chain - teasing rota shredder on each side - ideal for tight round bales	Bi directional chain - tease rota shredder on near side - 750mm extension for feeding into troughs on off side	Teasing elevator with Hydraulic sensing to offside with optional tease rota shredder to near side. Retarder bar fitted to elevator for square bales	Any type of the mentioned feed out chambers mounted to extended chasis for 3rd bale
BALE TYPES	Round Chopped Bales	Round and Square Bales	Round Bales any type	Round tight Bales	Round Bales + Squares achievable	All Rounds - Squares - Pit Silage	Feed-out as optioned
CROP TYPE	Silage bales	Silage / Hay / Straw bales	Silage / Hay / Straw bales	Silage / Hay / Straw bales	Silage bales	Silage / Hay / Straw bales	as optioned
HYDRAULIC CONTROL	2 x double acting	2 x double acting	2 x double acting	2 x double acting	2 x double acting	2 x double acting	2 x double acting
CAPACITIES IN kgs	2,000kgs	2,000kgs	2,200kgs	2,200kgs	2,000kgs	3,600kgs	3,600kgs
CAPACITIES 4' BALES	2	2	2	2	2	2	3
BODY LENGTH	1,465mm is our standard body size for 4' bales with all components jig built around this - we do offer optional 5' for bigger bales						
OVERALL LENGTH	4,030mm without loading tines	4,030mm without loading tines	4,030mm without loading tines	4,030mm without loading tines	4,030mm without loading tines	4,030mm without loading tines	5,230mm without loading tines
OVERALL WIDTH	2,280mm	2,280mm	2,290mm	2,300mm	2,650mm (as optioned)	2,300mm with extension verticle	as optioned
TARE WEIGHT	940kgs	880kgs	1,020kgs	1,100kgs	1,170kgs	1,630kgs as optioned	1,480kgs as optioned
SINGLE AXLE SIZE	50 / 6 Stud brakeless Rigid Axle	50 / 6 Stud brakeless Rigid Axle	50 / 6 Stud brakeless Rigid Axle	50 / 6 Stud brakeless Rigid Axle	50 / 6 Stud brakeless Rigid Axle	60 / 6 Stud brakeless Rigid Axle	60 / 6 Stud brakeless Rigid Axle
WHEELS	10.0 / 75 x 15.3 (see options)	10.0 / 75 x 15.3 (see options)	10.0 / 75 x 15.3 (see options)	10.0 / 75 x 15.3 (see options)	10.0 / 75 x 15.3 (see options)	11.5 / 80 x 15.3 (see options)	11.5 / 80 x 15.3 (see options)
CHASSIS	All chassis' are made of 152mm x 76mm - 400 grade RHS - fully welded to 4711 standard						
DRAW BAR LENGTH	1450mm with 60mm jack support	1450mm with 60mm jack support	1450mm with 60mm jack support	1450mm with 60mm jack support	1450mm with 60mm jack support	1450mm with 70mm jack support	1450mm with 70mm jack support
FLOOR THICKNESS	1.6mm Full steel floor	1.6mm Full steel floor	1.6mm Full steel floor	1.6mm Full steel floor	1.6mm Full steel floor	2mm Full steel floor	2mm Full steel floor
TOW EYE	All drawbars are fitted with a European 40mm diametre forged eye - options on swivel eye or variable height eyes are available						
HEADBOARD	Mesh with RHS rails	RHS twin rails	Mesh with RHS rails	RHS twin rails	Mesh with RHS rails	Mesh with RHS rails	as optioned
OIL REQUIREMENT	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 55 litres / minute	Minimum of 32 litres / minute
RAM	All feeder use a locally made 4" diametre hydraulic cylinder - double acting - it has a lift capacity of 1,850kgs with only 1,500PSI - ensuring all bales can be loaded						
LOADING	All Agmech feeders have a unique off ground loading system that has 2 x Swedish tines that pierce the bale 150mm from ground level thus eliminating tine damage but simplifying plastic and wrap removal - 2nd bale carried on tines awaiting feed-out						
FINISH	Blasted or solvent washed - heavy zinc based primer then 2 x gloss coats						
COLOUR	Agmech Yellow on body with Charcoal parts, wheels White						
OPTIONS	Common options are 400 wheels - twine box - we will gladly consider any other requirements that you have						