



Manufacturers of Agricultural Equipment



Specifications Jumbo STD J6



BODY TYPE:	Flat floor one piece monocoque body, with top pipe rails 3mm sheet steel with nominal spaced profiles supported by under sheet bracing
FEED OUT:	Single shredder either side, each offset to the floor chain as well as near side being lower than off side
HYDRAULIC CONTROL:	Controlled via the tractor remotes
CAPACITIES IN Kgs:	7200kgs
4' ROUND BALES:	5 up to 6' diameter
BODY LENGTH:	8,800mm
OVERAL LENGTH:	10,250mm
BODY WIDTH ID:	1,520mm at pipe rails

OVERAL WIDTH:	2,500mm at the shredders
AXLE TANDEM:	60mm / 6 stud brakeless Oscillating Axle
WHEELS TANDEM:	12.5 x 15.3
LOADING HEIGHT:	1,250mm
CHASSIS:	200 x 100 x 5mm fully welded chassis
HEADBOARD:	Removable headboard with rails
DRAW BAR LENGTH:	1,450mm fitted with 60mm jack support
SHUTTLE DRIVE:	Single 3:1 on 13mm chain
TOWING EYE:	Fixed eye
LOADING FOOT:	Drop down foot is ideal to rest the unit on when loading, it digs into the ground assisting when rear loading, used in conjunction with a quick hitch
FINISH/COLOUR:	Blasted, etch base zinc high build primer then dried. Followed by 2 x gloss coats of gloss paint Agmech Yellow, wheels white, door charcoal

NOTES: