

Specifications	Jumbo STD	Jumbo STD	Jumbo STD	Jumbo STD
MODELS	J4	J5	J6	J7
BODY TYPE	Flat Floor one piece monocoque with top pipe rails 3mm sheet steel with nominal spaced profiles supported by under sheet bracing			
FEEDOUT	Single shredder either side, each offset to the floor chain as well as near side being lower than off side			
HYDRAULIC CONTROL	Controlled via tractor remotes, with crossline relief on shuttle motor			
CAPACITIES IN kgs	4800kgs	6000kgs	7200kgs	8400kgs
CAPACITIES 4' ROUND BALES	4 up tp 6' diameter	5 up tp 6' diameter	6 up tp 6' diameter	7 up tp 7' diameter
BODY LENGTH	6300mm	7550mm	8800mm	10050mm
OVERALL LENGTH WITH DRAWBAR	7750mm	9000mm	10250mm	11500mm
BODY WITH ID	1,520mm	1,520mm	1,520mm	1,520mm
OVERALL WIDTH	Body 2,500mm at shredders	Body 2,500mm at shredders	Body 2,500mm at shredders	Body 2,500mm at shredders
AXLE TANDEM	50mm/6 stud brakeless Oscillating Axle	60mm/6 stud brakeless Oscillating Axle	60mm/6 stud brakeless Oscillating Axle	70mm/6 stud brakeless Oscillating Axle
WHEELS TANDEM	11.5 x 15.4	12.5 x 15.3	12.5 x 15.4	400 / 60 x 15.5
LOADING HEIGHT	1,150mm	1,200mm	1,250mm	1,300mm
CHASSIS	200 x 100 x 4mm fully welded chassis	200 x 100 x 5mm fully welded chassis	200 x 100 x 5mm fully welded chassis	200 x 100 x 6mm fully welded chassis
DRAW BAR LENGTH	1,450 mm fitted with 70mm support jack support	1,450 mm fitted with 80mm support jack support	1,450 mm fitted with 80mm support jack support	1,450 mm fitted with 80mm support jack support
SHUTTLE FLOOR	Single 3:1 on 10mm chain	Single 3:1 on 13mm chain	Single 3:1 on 13mm chain	Single 4:1 on 13mm chain
TOW EYE	Fixed eye	Fixed eye	Fixed eye	Fixed eye
HEADBOARD	Removable headboard with rails			
LOADING FOOT	Drop down foot is ideal to rest the unit on when loading, digs into ground assisting rear loading, used in conjunction with a quick hitch			
FINISH	Blasted, zinc base primer, 2 x gloss coats			
COLOUR	Standard Yellow	Standard Yellow	Standard Yellow	Standard Yellow
OPTIONS	Discuss your individual requirements with your dealer as a range of options are available.			