

Specifications	JUMBO TUB	JUMBO TUB	JUMBO TUB	JUMBO TUB
Models	JT 3	JT 4	JT 5	JT 6
FEED-OUT TYPE	Bi-directional via Single shredder on near side, with driven fixed elevator on offside ideal for chopped bales that fall to pieces and become hard to feed			
BALE TYPES	Chopped bales over curve bed Tight bales over rota shredder	Chopped bales over curve bed Tight bales over rota shredder	Chopped bales over curve bed Tight bales over rota shredder	Chopped bales over curve bed Tight bales over rota shredder
CROP TYPES	Round Silage / Hay / Straw bales	Round Silage / Hay / Straw bales	Round Silage / Hay / Straw bales	Round Silage / Hay / Straw bales
BODY TYPE	Tub body one piece monocoque, with top RHS rails 2mm sheet steel with nominal spaced profiles supported by under sheet bracing			
HYDRAULIC CONTROL	Controlled via tractor remotes to 2 x independent bidirectional hydraulic motors - shuttle drive has independent cross line relief valve			
CAPACITIES IN kgs	3600kgs	4800kgs	6000kgs	7200kgs
CAPACITIES 4' ROUND BALES	3 up to 6' diameter	4 up to 6' diameter	5 up to 6' diameter	6 up to 6' diameter
BODY LENGTH	5,050mm	7,000mm	7,550mm	8800mm
OVERALL LENGTH WITH DRAWBAR	6,560mm	8,450mm	9,000mm	10250mm
BODY WITH ID	2,000mm	2,000mm	2,000mm	2,000mm
OVERALL WIDTH	Body 2,667mm at widest	Body 2,667mm at widest	Body 2,667mm at widest	Body 2,667mm at widest
AXLE SINGLE	60mm/6 stud brakeless Rigid Axle	70mm/6 stud brakeless Rigid Axle	X	X
WHEELS SINGLE	11.5 / 75 x 15.3	400 / 60 x 15.5 traction wheel	X	X
AXLE TANDEM	X	50mm/6 stud brakeless Oscillating Axle	60mm/6 stud brakeless Oscillating Axle	70mm/6 stud brakeless Oscillating Axle
WHEELS TANDEM	X	11.5 / 75 x 15.3	12.5 / 75 x 15.3	400 / 60 x 15.5
LOADING HEIGHT	1,500mm	1,550mm	1,600mm	1,650
CHASSIS	200 x 100 x 4mm fully welded chassis	200 x 100 x 5mm fully welded chassis	200 x 100 x 5mm fully welded chassis	200 x 100 x 6mm fully welded chassis
DRAW BAR LENGTH	1,450mm as standard with option for 1,750mm for wide track tractor or 2,050mm for tractors running dual wheels			
FLOOR THICKNESS	2mm mild steel	2mm mild steel	2mm mild steel	2mm mild steel
TOW EYE	X	Fixed eye	Fixed eye	Swivel 43mm eye
HEADBOARD	Full mesh Headboard with RHS top rail and frame giving optimum visibility			
LOADING FOOT	Optional drop down foot is ideal to rest the unit on when loading, digs into ground assisting rear loading, used in conjunction with a quick hitch or support jack as standard			
FINISH	Blasted, zinc base primer, 2 x gloss coats			
COLOUR	Standard Yellow	Standard Yellow	Standard Yellow	Standard Yellow
OPTIONS	Discuss your individual requirements with your dealer as a range of options are available.			