

Specifications	Linkage	Linkage	Linkage	Linkage	Linkage
MODELS	Double Curve	RS1	Single Shredder	Twin Shredder	Trough Feeder
FEED-OUT TYPE	Bi directional chain - on symetrical high curve - ideal for all chopped round bales	Bi directional chain - on symetrical low curve - Retarder bar fitted to both sides for square bales	Bi directional chain - teasing rota shredder on near side - high curve on off side	Bi directional chain - teasing rota shredder on each side - ideal for tight round bales	Bi directional chain - tease rota shredder on near side - 750mm extension for feeding into troughs on off side
BALE TYPES	Round Chopped Bales	Round and square bales	Round Bales any type	Round tight bales	Round Bales + Squares achievable
CROP TYPE	Silage bales	Silage / Hay / Straw bales	Silage / Hay / Straw bales	Silage / Hay / Straw bales	Silage bales
HYDRAULIC CONTROL	1 x double acting	1 x double acting	1 x double acting	1 x double acting	1 x double acting 1 x double for folding
CAPACITIES IN kgs	1,100kgs	1,100kgs	1,100kgs	1,100kgs	1,100kgs
CAPACITIES 4' BALES	1	1	1	1	1
BODY LENGTH	2,400mm	2,400mm	2,400mm	2,400mm	2,400mm
BODY WIDTH	2,280mm	2,280mm	2,290mm	2,300mm	2,300mm with extension verticle
TARE WEIGHT	540kgs	570kgs	620kgs	710kgs	850kgs
CHASSIS	75mm x 75mm 400 grade RHS fully welded to 4711 standard				
FLOOR THICKNESS	1.6mm steel floor with nominal bracing underneath as well as rub bars on top				
HEADBOARD	Mesh headboard	Pipe Headboard	Mesh headboard	Pipe Headboard	Pipe Headboard
OIL REQUIREMENT	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 32 litres / minute	Minimum of 32 litres / minute
LOADING	75mm x 75mm 400 grade RHS fully welded to 4711 standard				
FINISH	Blasted, zinc base primer, 2 x gloss coats				
COLOUR	Agmech Yellow on body with charcoal components and white comb				
OPTIONS	Discuss your individual requirements with your dealer as a range of options are available.				