

<b>Specifications</b>	<b>Rotary Manure Spreader</b>	<b>Rotary Manure Spreader</b>	<b>Rotary Manure Spreader</b>	<b>Rotary Manure Spreader</b>
<b>MODELS</b>	<b>MM400</b>	<b>MM600</b>	<b>MM800T</b>	<b>MM1000T</b>
BODY TYPE	Fully welded monocoque body	Fully welded monocoque body	Fully welded monocoque body	Fully welded monocoque body
CAPACITY TONNES	6 tonnes	8 tonnes	10 tonnes	12 tonnes
CUBIC CAPACITY	4.0m <sup>3</sup>	6.0m <sup>3</sup>	8.0m <sup>3</sup>	10.0m <sup>3</sup>
LIQUID CAPACITY	3,000 litres (with 200mm hungry board fitted)	5,000 litres (with 200mm hungry board fitted)	6,500 litres (with 200mm hungry board fitted)	8,000 litres (with 200mm hungry board fitted)
BODY LENGTH	3,000mm	3,600mm	3,900mm	4,200mm
OVERALL LENGTH	4,750mm	5,350mm	5,650mm	5,950mm
BARRELL DIAMETRE	1.32mØ barrel	1.46mØ barrel	1.60mØ barrel	1.70mØ barrel
OVERALL WIDTH	2,000mm depending on wheels	2,150mm depending on wheels	2,400mm depending on wheels	2,600mm depending on wheels
OVERALL HEIGHT	1,950mm depending on wheels	2,100mm depending on wheels	2,250mm depending on wheels	2,350mm depending on wheels
AXLE SINGLE	70mm / 6 stud	80mm / 8 stud	X	X
AXLE TANDEM	50mm / 6 stud	60mm / 6 stud	70mm / 6 stud	80mm / 8 stud
WHEELS ON SINGLE	400 / 60 x 15.5 - 14 ply	385 / 65 x 22.5	X	X
WHEELS ON TANDEM	10.0 / 75 x 15.3 - 12 ply	11.5 / 80 x 15.3	400 / 60 x 15.5 - 14 ply	385 / 65 x 22.5
SUSPENSION	Rigid or oscillating tandem	Rigid or oscillating tandem	Oscillating tandem	Oscillating tandem
LID	Manual opening / hydraulic optional	Manual opening / hydraulic optional	Hydraulic optional	Hydraulic optional
MUDGUARDS	Optional	Optional	Options	Standard
CHASSIS	200 x 100 x 6 RHS	200 x 100 x 6 RHS	200 x 100 x 9mm RHS	250 x 150 x 6 RHS
BARRELL SPEC	4mm barrel with 5mm end plates	4mm barrel with 6mm end plates	5mm barrel with 6mm end plates	6mm barrel with 6mm end plates
ROTA SPEC	100 x 100 x 6 RHS with 10mm chain	100 x 100 x 6 RHS with 10mm chain	100 x 100 x 9 RHS with 40 x 13mm chain	100 x 100 x 9 RHS with 13mm chain
GEARBOX	3 : 1 reduction on 3/4" duplex drive	3 : 1 reduction on 3/4" duplex drive	3 : 1 reduction on 3/4" Triplex drive	3 : 1 reduction on 5/8" Triplex drive
PTO	Wide angle PTO with 6 spline both ends	Wide angle PTO with tractor 6 spline & 20 spline on drive	Wide angle PTO with tractor 6 spline & 20 spline on drive	Wide angle PTO with tractor 20 spline on each end
DRAWBAR SUPPORT	60mm jack	70mm jack	80mm jack	100mm jack
TOW EYE	fixed 50 eye	fixed 50 eye	Swivel 43mm eye	Swivel 50mm eye
FINISH	Blasted, heavy coat of primer then 2 x gloss coat	Blasted, heavy coat of primer then 2 x gloss coat	Blasted, heavy coat of primer then 2 x gloss coat	Blasted, heavy coat of primer then 2 x gloss coat
COLOUR	Agmech Yellow / charcoal / wheels white	Agmech Yellow / charcoal / wheels white	Agmech Yellow / charcoal / wheels white	Agmech Yellow / charcoal / wheels white
OPTIONS	Discuss your individual requirements with your dealer as a range of options are available.			